GENERAL NOTES

COMMUNICATION SYSTEMS

- 1. NOT ALL EXISTING EQUIPMENT IS SHOWN. CONTRACTOR SHALL FIELD VERIFY ACTUAL EXISTING CONDITIONS.
- 2. AT ALL WORK LOCATIONS, THE FOLLOWING EXISTING EQUIPMENT SHALL BE SALVAGED AS DIRECTED BY THE ENGINEER:
 - ALL NEXTBUS LED SHELTER DISPLAYS, MOUNTING BRACKETS, AND POWER SUPPLY.
 - ALL CLEAR CHANNEL SHELTER AD PANEL DISPLAYS
- 3. ALL PROVIDED CABINETS AND RACKS SHALL BE SEISMICALLY BRACED. SEE STRUCTURAL SECTION FOR DETAILS.
- 4. ALL DIMENSIONS SHOWN ARE APPROXIMATE AND DIAGRAMMATIC. DRAWINGS ARE NOT TO SCALE. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL FIELD VERIFICATION AND SUBMIT SHOP DRAWINGS FOR APPROVAL PRIOR TO CONSTRUCTION.
- 5. CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING WITH THE ENGINEER TO DE-ENERGIZE THE OVERHEAD CONTACT SYSTEM PRIOR TO PROCEEDING WITH ANY WORK LOCATED RADIALLY WITHIN 6 FEET (RADIALLY 10 FEET FOR VERTICALLY MOVING BOOM TYPE EQUIPMENT) OF THE OVERHEAD CONTACT SYSTEM. REFER TO SPECIFICATIONS SPECIAL PROVISIONS SECTION FOR DETAILS.
- 6. PRIOR TO BEGINNING ANY WORK IN ANY AND ALL EQUIPMENT ROOMS, PROVIDE TEMPORARY PROTECTIVE BARRIERS AROUND TRAIN CONTROL EQUIPMENT AS INDICATED. VERIFY WITH THE ENGINEER THAT ALL TRAIN CONTROL EQUIPMENT IS PROPERLY PROTECTED BEFORE PROCEEDING WITH WORK.
- 7. IN VAN NESS STATION EQUIPMENT ROOM, NETWORK EQUIPMENT CABINET HAS LIVE NETWORK TRAFFIC. CONTRACTOR ONLY PERFORM APPROVED WORK WITH SFMTA REPRESENTATIVE PRESENT.
- 8. NEW COMMUNICATIONS CABLES: REFER TO STATION'S CABLE PLANS AND CABLE SCHEDULES FOR COMPLETE REQUIREMENTS. CAUTION: NOT ALL NEW COMMUNICATION CABLES (AS NOTED IN CABLE SCHEDULE "CONTRACTOR'S DISCRETION") ARE SHOWN ON LAYOUT DRAWINGS.
- 9. CABLE RUNS BETWEEN NETWORK SWITCHES AND CCTV, TVM, PA SPEAKERS SHALL BE CAT-6.
- 10. ALL RJ45 CONNECTORS EXTERNAL TO COMMUNICATIONS CABINET SHALL BE WATERPROOF AND RATED IP67.
- 11. APPROVED INLINE POE ETHERNET EXTENDER SHALL BE INSTALLED FOR ALL ETHERNET LINKS MORE THAN 300 FEET. ETHERNET EXTENDERS SHALL BE RATED IP66 MINIMUM. EXTENDERS SHALL BE MOUNTED ON GALVANIZED DIN RAIL OR STRUT CHANNEL SECURED TO SIDE OF PULLBOXES.
- 12. CONTRACTOR SHALL TEST CERTIFY ALL FIBER CABLES AND CAT-6 CABLES INSTALLED TO MEET OR EXCEED TIA/EIA-568-C. ALL CABLE PERFORMANCE PARAMETERS DEFINED IN TIA/EIA-568-C SHALL BE MEASURED AND RECORDED FOR EACH CABLE. CONTRACTOR SHALL SUBMIT CABLE CERTIFICATION DATA IN APPROVED ELECTRONIC FORMAT TO ENGINEER.

FIBER NETWORK

- 1. DO NOT DISTURB FIBERS WITH LIVE TRAFFIC, WITHOUT APPROVED MIGRATION STEPS AND BACKUP PLAN.
- 2. COORDINATE WITH SFMTA-IT DEPARTMENT FOR ALL FIBER TERMINATIONS TO EQUIPMENT.

WIRING AND ROUTING

- 1. ALL NEW RACEWAY, I.E. CONDUIT, ETC., ROUTING ARE SCHEMATICALLY AND DIAGRAMMATICALLY SHOWN. PRIOR TO ANY WORK, CONTRACTOR SHALL FIELD VERIFY ALL EXISTING CONDITIONS, ROUTE AND INSTALL NEW RACEWAY AND RELATED MATERIALS I.E. BOXES, ETC., PER NEC AND IN WORKMANLIKE MANNER.
- 2. SHOP DRAWINGS: PRIOR TO ANY WORK, CONTRACTOR SHALL SUBMIT SHOP DRAWINGS TO ENGINEER FOR REVIEW AND APPROVAL. SHOP DRAWINGS SHALL INCLUDE, BUT NOT LIMITED TO, THE FOLLOWING:
 - CABINET CONFIGURATION, EQUIPMENT MOUNTING DETAILS, GROUNDING/ BONDING DETAILS, ELECTRICAL SINGLE LINE DIAGRAM.
 - PULLBOX CONFIGURATION DETAILS, CONDUIT/ RACEWAY ROUTING DETAILS, CABLE/ WIRING ROUTING DETAILS.
 - EQUIPMENT SCHEDULE, MATERIAL SCHEDULE, FIBER ASSIGNMENTS, EQUIPMENT PORT ASSIGNMENTS, AND LABEL SCHEDULE AT EACH STATION LOCATION.
 - PLAN VIEW THAT SHOWS COMMUNICATIONS CABINET, ELECTRICAL PANEL CABINET, AND TRAFFIC COTNROLLER CABINET, AND RELATED PULL BOXES AT EACH STATION LOCATION.
 - LOCATIONS OF ALL POE ETHERNET EXTENDERS AND EXTENDER MOUNTING DETAILS.
 - ALL RACEWAY SYSTEM (INCLUDING ALTERNATE ROUTING AND RACEWAY MATERIALS FINISHES) IN ACCORDANCE WITH SPECIFICATION SECTION 16110 AND 16130.
- 3. REFERENCE DRAWINGS: REFERENCE DRAWINGS ARE PROVIDED TO IDENTIFY ELEVATIONS, LOCATIONS OF CONCEALED SPACES, AND CEILING ASSEMBLIES. CONTRACTOR SHALL PERFORM EXISTING CONDITION SURVEY WHICH INCLUDES FIELD INVESTIGATION OF EXISTING CONCEALED SPACES FOR INSTALLATION OF NEW RACEWAYS, CABLES, SUPPORTS, ETC. IN ADDITION, CONTRACTOR SHALL PREPARE RACEWAY SHOP DRAWINGS FOR REVIEW AND APPROVAL PRIOR TO ANY WORK.
- 4. POWER AND COMMUNICATION WIRING CONNECTIONS TO NEW EQUIPMENT CABINETS AND RACKS SHALL BE WIRED WITH SUFFICIENT LENGTHS SO THAT WHEN EQUIPMENT MOVES FROM TEMPORARY TO PERMANENT LOCATION, THERE WILL BE MINIMUM REWIRING. CONTRACTOR SHALL PROVIDE FLEXIBLE CONDUIT OR CABLE TRAY FOR WIRING CONNECTIONS AT TEMPORARY AND PERMANENT LOCATION. REFER TO SPECIFICATION'S SPECIAL PROVISION FOR RESTRICTION AND OTHER REQUIREMENTS. RACEWAYS SHALL BE PROPERLY SUPPORTED PER NEC.
- 5. ALL RACEWAYS IN PUBLIC AREAS SHALL BE CONCEALED UNLESS OTHERWISE NOTED OR APPROVED BY THE ENGINEER. POWER AND COMMUNICATION EXPOSED RACEWAYS (CONDUITS, WIREWAY, SURFACE METAL RACEWAY, ETC.) IN ANY PUBLIC AREAS CONTRACTOR SHALL PAINT RACEWAYS AND HARDWARE TO MATCH EXISTING PAINTED HARD SURFACES. CONTRACTOR SHALL SUBMIT PROPOSED RACEWAY FINISHES FOR APPROVAL.
- 6. CORE DRILLING: CONTRACTOR SHALL CORE DRILL AS REQUIRED FOR ROUTING OF RACEWAY THROUGH WALLS, FLOORS AND CEILINGS. CAUTION: NOT ALL REQUIRED CORE DRILLINGS ARE NOTED ON LAYOUT DRAWINGS. CORE DRILL LOCATIONS SHOWN ARE SUGGESTED. CONTRACTOR SHALL FIELD VERIFY AND LOCATE HIS PROPOSED CORE DRILL LOCATIONS. PERFORM X-RAY SURVEY AT CONTRACTOR'S PROPOSED CORE DRILL LOCATIONS TO AVOID REBAR DAMAGE.
- 7. EXISTING SPARE CONDUITS: WHERE INDICATED TO INSTALL NEW WIRES, CONTRACTOR SHALL USE MANDREL TO TEST SPARE CONDUITS TO ENSURE THAT NEW WIRES CAN BE INSTALLED. NOTIFY SFMTA IMMEDIATELY IF CONDUIT IS OBSTRUCTED.

ELECTRICAL

- 1. ELECTRICAL WIRING SHALL BE SOLID COPPER, #10 AWG MINIMUM. WIRES SHALL BE XHHW-2 AND CABLES SHALL BE TYPE UF-B UNLESS INDICATED OTHERWISE.
- 2. CONTRACTOR SHALL PERFORM DC RESISTANCE TEST AND INSULATION RESISTANCE TEST ON ALL ELECTRICAL WIRING INSTALLED. MEASUREMENT RESULTS SHALL MEET OR EXCEED MANUFACTURER SPECIFICATIONS. CONTRACTOR SHALL SUBMIT TEST CERTIFICATION DATA IN APPROVED ELECTRONIC FORMAT TO ENGINEER.
- 3. ALL HDPE DUCT SHALL BE SCHEDULE 40 IN 40 FOOT STICK TYPE LENGTHS. HDPE IN CONTINUOUSLY REELED ARE NOT ACCEPTABLE.
- 4. CONTRACTOR SHALL PROVIDE A CONTINUOUS GROUND WIRE WITH THE PHASE CONDUCTOR IN THE SAME CONDUIT. GROUNDING USING CONDUIT ARE NOT ACCEPTABLE.

GENERAL

- 1. INSTALLATION, WORKMANSHIP, AND PROJECT MATERIALS SHALL COMPLY WITH NATIONAL ELECTRIC CODE, LOCAL, STATE, AND FEDERAL CODES.
- 2. GENERAL WORK PRACTICES FOR ELECTRICAL CONSTRUCTION SHALL BE IN ACCORDANCE WITH NECA 1-2010, STANDARD FOR GOOD WORKMANSHIP IN ELECTRICAL CONSTRUCTION (ANSI).
- 3. WHEN REQUIREMENTS CONFLICT, THE MORE STRINGENT REQUIREMENT SHALL APPLY.
- 4. ALL NEW COMMUNICATIONS AND ELECTRICAL EQUIPMENT SHALL BE ANCHORED PER STRUCTURAL DRAWINGS AND AS RECOMMENDED BY MANUFACTURER.
- 5. COORDINATE ALL WORK WITH ALL OTHER DISCIPLINES, INCLUDING PLANS TO BE PROVIDED BY CONTRACTOR. FOR DUCT CONFIGURATION, SEE JT DRAWINGS. FOR TRAFFIC SIGNALS PULL BOXES, POLES, AND WIRING, SEE ET DRAWINGS.
- 6. CONTRACTOR TO COORDINATE WITH PG&E FOR ALL NEW METERED SERVICE. CORE DRILL THE PG&E MANHOLE OR HANDHOLE FOR THE NEW 3" HDPE CONDUIT ENTRANCE.
- 7. FOR GUARD RAIL, SEE ARCHITECTURAL AR SERIES FOR EXACT LOCATIONS AND POWER DISTRIBUTION.
- 8. ALL CAST IRON METALLIC BOXES AT THE BOARDING ISLANDS SHALL HAVE ONE INCH OPENING AT THE BOTTOM OF THE BOXES FOR DRAINAGE.
- 9. THE N36 AND P36 CONCRETE BOXES SHALL INCLUDE EXTENSIONS, R-SERIES COMPOSITE LIDS, STEEL CHECKER PLATE BOLT DOWN COVERS, N90 BOLT DOWN KITS. THE N36 SHALL BE MARKED "MTA POWER", THE P36 SHALL BE MARKED "MTA 311 PHONE" FOR PHONE, AND P36 BE MARKED "MTA NETWORK" FOR COMMUNICATION.
- 10. ALL CONCRETE PULL BOXES ON THE SIDEWALK AND ALL CAST IRON METALLIC PULL BOXES ON THE BOARDING ISLANDS SHALL INCLUDE CRUSHED ROCK SUMP WITH MINIMUM 6" DEPTH AND THE BOTTOM AREA OF 6" BEYOND THE BOX OUTSIDE DIMENSIONS OF PULL BOXES PER THE CALTRANS STANDARD PLAN RSP FS-8A
- 11. CONTRACTOR TO COORDINATE WITH SFMTA IT DEPARTMENT, SFMTA VIDEO SHOP FOR SETTING UP, CONFIGURATION AND TESTING OF THE DIGITAL VIDEO RECORDERS, SERVERS FOR THE CCTV SYSTEM, PA SYSTEM, AND ALL NETWORK DEVICES.

NO. DATE DESCRIPTION REVISED CHECKED APPROVED


REVISIONS

DESIGNED

DRAWN

CHECKED

CHEC





CITY AND COUNTY OF SAN FRANCISCO
MUNICIPAL TRANSPORTATION AGENCY

APPROVED

June 1, June

for the DIRECTOR OF TRANSPORTATION

VAN NESS CORRIDOR TRANSIT IMPROVEMENT PROJECT

COMMUNICATIONS AND NETWORKING GENERAL NOTES CL-29030

CN-G1

CN-G2

O

LEGEND

FIBER PATCH PANEL	FIBER PATCH PANEL/ DISTRIBUTION PANEL		
			NEW EQUIPMENT — FINAL LOCATION MAY BE CHANGED ONCE SPACE IS VACATED BY DEMOLISHED EQIUPMENT
			EQUPMENT TO BE DEMOLISHED/ SALVAGED
——F0——	2" HDPE CONDUIT FOR FIBER OPTIC CABLE		
— N — N —	2" HDPE CONDUIT FOR CAT 6 & TSP PHONE WIRE	111///	ARCHITECTURAL FEATURE, SEE ARCHITECTURAL DRAWINGS
— P - P —	2" HDPE CONDUIT FOR ELECTRICAL POWER		
-T -T -	2" HDPE CONDUIT FOR AT&T PHONE	₩ _P	WATER PROOF GFCI RECEPTACBLE WITH LOCKING COVER
	STRAIGHT FUSION SPLICE IN FIBER OPTIC PANEL	фА, фС	PHASE A OR PHASE C OF THE 120/ 240VAC
-	PATCH CORD/ PIGTAIL TERMINATION IN P/P		
	EXISTING/ NIC (NOT IN CONTRACT)		
S	PUBLIC ADDRESS SPEAKER		CCTV CAMERA
	JUNCTION BOX		
N	COMMUNICATIONS PULL BOX		DETAIL BOUNDARY MARKERS
Р	ELECTRICAL PULL BOX	PP	COMMUNICATIONS AND ELECTRICAL PANEL CABINET AND PULL BOXES
T	TELEPHONE PULL BOX	CC	COMMUNICATIONS CABINET
		EC	ELECTRICAL CABINET

ABBREVIATIONS

PATCH PANEL PUBLIC ADDRESS


POWER CONTROL CENTER


PROGRAMMABLE LOGIC CONTROLLER


311 & AC AIC A, AMP ANSI A/V AVE AWG	COURTESY PHONE AND ALTERNATING CURRENT AVAILABLE INTERRUPTING CAPACITY AMPERES AMERICAN NATIONAL STANDARD INSTITUTE AUDIO/VISUAL OR AUDIO/VIDEO AVERAGE AMERICAN WIRE GAUGE	P/P PA PCC PLC PNL PoE R&D R&S REL
BART BAT, BATT	BAY AREA RAPID TRANSIT BATTERY	REPL RSC RTU
CAB CB CC CCTV CKT COMM, CN COMM CAB COMP	CABINET CIRCUIT BREAKER COMMUNICATIONS CABINET CLOSED CIRCUIT TELEVISION CIRCUIT COMMUNICATION COMMUNICATIONS CABINET COMPUTER	RX SCADA SFMTA SM SPKR SVN SW
DC DEST DISTR, DIST DT DTS	DIRECT CURRENT DESTINATION DISTRIBUTION DEPARTMENT OF TECHNOLOGY DATA TRANSMISSION SYSTEM	TBD TEL TMC TSP TV TVM
(E) EC ECB ELEC. , EL EMER. ENET EP EQUIP, EQPT, EQMT	EXISTING ELECTRICAL CABINET ENCLOSED CIRCUIT BREAKER ELECTRICAL EMERGENCY ETHERNET ELECTRICAL PANEL EQUIPMENT	UON UPS UTP V VIF VolP
F/I FLR FO	FURNISH AND INSTALL FLOOR FIBER OPTIC	W
GFCI GND, G GRS	GROUND FAULT CIRCUIT INTERUPTER GROUND GALVANIZED RIGID STEEL	
HDPE HZ	HIGH DENSITY POLYETHYLENE HERTZ	
I/O IP IT	INPUT/OUTPUT INTERNET PROTOCOL INFORMATION TECHNOLOGY	
JB	JUNCTION BOX	
KVA KW	KILO-VOLT-AMPERES KILO-WATTS	
LAN LSZH LTG	LOCAL AREA NETWORK LOW SMOKE ZERO HALOGEN LIGHTING	
MCB MEZZ MIC MIN MM MM	MAIN CIRCUIT BREAKER MEZZANINE MICROPHONE MINIMUM MULTI-MODE FIBER MUNICIPAL RAILWAY	
(N) NECA NO NC NS	NEW NATIONAL ELECTRICAL CONTRACTOR ASSOCIATION NORMALLY OPEN NORMALLY CLOSED NOISE SENSING	
OCC OSVN/1SVN	OPERATIONS CONTROL CENTER ONE SOUTH VAN NESS	
Р	POLE (CIRCUIT BREAKER)	

POWER OVER ETHERNET
REMOVE AND DISPOSE REMOVE AND SALVAGE RELOCATE REPLACEMENT RIGID STEEL CONDUIT REMOTE TERMINAL UNIT RECEIVE
SUPERVISORY CONTROL AND DATA ACQUISITION SYSTEM SAN FRANCISCO MUNICIPAL TRANSPORTATION AGENCY SINGLE MODE FIBER SPEAKER SOUTH VAN NESS SWITCH
TO BE DETERMINED TELEPHONE TRANSPORTATION MANAGEMENT CENTER TWISTED PAIR TELEVISION TICKET VENDING MACHINE
UNLESS OTHERWISE NOTED UNINTERRUPTIBLE POWER SUPPLY UNSHIELDED TWISTED PAIR
VOLT VERIFY IN FIELD VOICE OVER IP
WATTS

REVISED CHECKED APPROVED DESCRIPTION NO. DATE REVISIONS









for the DIRECTOR OF TRANSPORTATION


	MUNI	BUS	RAPID	TRANSIT	SYSTEM	
S	CORRI	DOR	TRANS	SIT IMPI	ROVEMENT	PRC

1289 CL-29031

STATION SYSTEMS ELECTRICAL LEGENDS AND ABBREVIATIONS

CN-G2

BORDER REVISED 11/17/05




				,								<u> </u>	
Location: Van Ness and Marke	et		Main I	Breake	er: 200/	A				Enclosure mounting: Pad mounted			
Phase: 1			Main I	Lug: N	/A					NEMA: 4	<		
wires: 3			Bus: 2	200A						AIC: 22,00	DOA		
	V	' A								VA			
Description	ØΑ	ØС	Bkr	Ckt	фА	, ф	C	Ckt	Brk	ØΑ	ØС	Description	
spare	500		20	1				2	20	500		Uninterruptable power supply	
spare		500	20	3				4	20		500	spare	
spare	500		20	5		•		6	20	500		spare	
spare		500	20	7				8	20		500	Comm cabinet, receptacle	
spare	500		20	9		V		10	20	500		spare	
variable message sign (SN #3)		500	50	11		6		12	20		500	spare	
SFMTA display, southbound	500		20	13				14	20	500		SFMTA display, northbound	
NextBus display, southbound		500	20	15				16	20		500	NextBus display, northbound	
TVM, southbound	500		20	17				18	20	500		TVM, northbound	
311 phone, southbound		500	20	19		6		20	20		500	3ll phone, northbound	
shelter lights, southbound	500		20	21				22	20	500		shelter lights, northbound	
guard rail lights, southbound		500	20	23		4		24	20		500	guard rail lights, northbound	
irrigation southbound (SN#2)	500		20	25				26	20	500		irrigation northbound (SN#2)	
spare		500	20	27				28	20		500	spare	
Golden Gate sign, southboun	500		20	29				30	20	500		Golden Gate sign, northbound	
Art work tower SB (SN#4)		500	30	31				32	30		500	Art work tower NB (SN#4)	
spare	500		20	33				34	20	500		spare	
spare		500	20	35		4		36	20		500	spare	
subtotal	4500	4500								4500	4500	subtotal	
			anni e Tarquenia e e e e e e e e e e e e e e e e e e e			turnovane voja garan		•					
Lighting load VA: 2,000							Tota	VA p	er ph	ase: ØA = 9	9,000 ØI	B = 9,000	
Receptacle load VA: 500	en e		ggalaginis kanan mengadi bigi kanan keta perilang dan anaka 90 km manggal		KON OON AG OOR OF BUT ON THE STREET OF T			Marie Commence of the Commence		d load VA:			
							T-						


Mfg / Type: GE or Square D

- 1. The above electrical panel is at Van Ness and Market (VNM), typical for locations at McAllister (VNMa), Eddy (VNE), Geary (VNG),
- 3. Provide 1P50A circuits to variable message signs from panels VNG (see ET-133) and VNJ (see ET-134).


	DESIGNED Meuny DRAWN CHECKED PROFESS 10Ny CHECKED PROFESS 10Ny CHECKED PROFESS 10Ny CHECKED CHECKED	CITY AND COUNTY OF SAN FRANCISCO MUNICIPAL TRANSPORTATION AGENCY	MUNI BUS RAPID TRANSIT SYSTEM VAN NESS CORRIDOR TRANSIT IMPROVEMENT PROJECT	1289 CL-29032
DESCRIPTION REVISED CHECKED APPROVED REVISIONS	RECOMMENDED TO TO THE MAY 18 2016 NOT VALID UNLESS SIGNED	APPROVED VILLET AND for the DIRECTOR OF TRANSPORTATION	COMMUNICATION SYSTEM BLOCK DIAGRAM AND TYPICAL ELECTRICAL PANEL SCHEDULE	CN-01 REVISION O




. .





ıV.






.







w\



1) Ash




. 11



۸۷,

- 1. SEE DWG CN-01 FOR VNMa ELECTRICAL PANEL SCHEDULE.
- 2. FOR EXACT LOCATIONS OF THE ELECTRICAL EQUIPMENT, SEE ARCHITECTURAL AR SERIES DRAWINGS.
- 3. THE APPROXIMATE DISTANCE FROM THE COMMUNICATION/ELECTRICAL CABINETS TO THE FIRST PULL BOX AT THE NORTHBOUND BOARDING PLATFORM IS 70 FEET.
- 4. ALL PULL BOXES ON THE BOARDING PLATFORMS SHALL BE OZ GEDNEY CAT# YU-161208. SEE ARCH. DWGS FOR BOX LOCATIONS AND QUANTITY OF BOXES.
- 5. SEE UTILITY COMPOSITE UT SERIES DRAWINGS FOR FIBER OPTIC CONDUITS IN COMMON TRENCH AT WEST SIDE OF VAN NESS CORRIDOR.
- 6. MOUNT PA SPEAKERS ON BUS SHELTERS OR CCTV POLES AS DIRECTED BY ENGINEER DURING CONSTRUCTION.
- 7. INSTALL 311 PHONE WIRING VIA NETWORK CONDUITS.

- 8. FOR 311 PHONE INTERCONNECTION BETWEEN STATIONS, SEE TELEPHONE DISTRIBUTION COMPOSITE, DWG CN-027.
- 9. CONTRACTOR TO ORDER ONE AT&T LANDLINE PER 311 PHONE PEDESTAL ON EACH BOARDING ISLAND. TOTAL OF EIGHTEEN (18) AT&T LANDLINES FOR THE 311 PHONE PEDESTALS.
- 10. FOR IRRIGATION POWER AND VARIABLE MESSAGE SIGN POWER, SEE IRRIGATION AND VMS DISTRIBUTION COMPOSITE, DWG CN-028.
- 11. ALL CONCRETE PULL BOXES IN THE SIDEWALK SHALL BE CHRISTY N36 FOR ELECTRICAL POWER, CHRISTY P36 FOR TELEPHONE AND NETWORK SYSTEMS.
- 12. ALL CONDUITS BETWEEN METAL PULL BOXES SHALL BE 1 1/2" HDPE. ALL ABOVE GROUND RIGID CONDUITS SHALL BE 1" RSC IN THE BUS SHELTERS AND SHALL BE CONCEALED. EXPOSED RSC CONDUITS SHALL BE APPROVED BY ENGINEER.



NOT VALID UNLESS SIGNED

BORDER REVISED 11/17/05

DESCRIPTION

REVISIONS

REVISED CHECKED APPROVE


NO. DATE

for the DIRECTOR OF TRANSPORTATION

BOARDING ISLAND LAYOUT -MCALLISTER STREET STATION NORTHBOUND

CL-29039 CN-11

CN-31



- 1. SEE DWG CN-01 FOR VNE ELECTRICAL PANEL SCHEDULE.
- 2. FOR EXACT LOCATIONS OF THE ELECTRICAL EQUIPMENT, SEE ARCHITECTURAL AR SERIES DRAWINGS.
- 3. THE APPROXIMATE DISTANCE FROM THE COMMUNICATION/ELECTRICAL CABINETS TO THE FIRST PULL BOX AT THE NORTHBOUND BOARDING PLATFORM IS 70 FEET.
- 4. ALL PULL BOXES ON THE BOARDING PLATFORMS SHALL BE OZ GEDNEY CAT# YU-161208. SEE ARCH. DWGS FOR BOX LOCATIONS AND QUANTITY OF BOXES.
- 5. SEE UTILITY COMPOSITE UT SERIES DRAWINGS FOR FIBER OPTIC CONDUITS IN COMMON TRENCH AT WEST SIDE OF VAN NESS CORRIDOR.
- 6. MOUNT PA SPEAKERS ON BUS SHELTERS OR CCTV POLES AS DIRECTED BY ENGINEER DURING CONSTRUCTION.

MUNI BUS RAPID TRANSIT SYSTEM

VAN NESS CORRIDOR TRANSIT IMPROVEMENT PROJECT

BOARDING ISLAND LAYOUT -

EDDY STREET STATION NORTHBOUND

1289

CL-29041


CN-13

CN-31

REVISION

7. INSTALL 311 PHONE WIRING VIA NETWORK CONDUITS.

- 8. FOR 311 PHONE INTERCONNECTION BETWEEN STATIONS, SEE TELEPHONE DISTRIBUTION COMPOSITE, DWG CN-027.
- 9. CONTRACTOR TO ORDER ONE AT&T LANDLINE PER 311 PHONE PEDESTAL ON EACH BOARDING ISLAND. TOTAL OF EIGHTEEN (18) AT&T LANDLINES FOR THE 311 PHONE PEDESTALS.
- 10. FOR IRRIGATION POWER AND VARIABLE MESSAGE SIGN POWER, SEE IRRIGATION AND VMS DISTRIBUTION COMPOSITE, DWG CN-028.
- 11. ALL CONCRETE PULL BOXES IN THE SIDEWALK SHALL BE CHRISTY N36 FOR ELECTRICAL POWER, CHRISTY P36 FOR TELEPHONE AND NETWORK SYSTEMS.
- 12. ALL CONDUITS BETWEEN METAL PULL BOXES
 SHALL BE 1 1/2" HDPE. ALL ABOVE GROUND
 RIGID CONDUITS SHALL BE 1" RSC IN THE BUS
 SHELTERS AND SHALL BE CONCEALED. EXPOSED
 RSC CONDUITS SHALL BE APPROVED BY ENGINEER.



MAY 1 9 2016

NOT VALID UNLESS SIGNED

CITY AND COUNTY OF SAN FRANCISCO
MUNICIPAL TRANSPORTATION AGENCY

for the DIRECTOR OF TRANSPORTATION

424


NO. DATE

BORDER REVISED 11/17/05

DESCRIPTION

REVISIONS


REVISED CHECKED APPROVE



'N'

- SEE DWG CN-01 FOR VNG ELECTRICAL PANEL SCHEDULE.
- 2. FOR EXACT LOCATIONS OF THE ELECTRICAL EQUIPMENT, SEE ARCHITECTURAL AR SERIES DRAWINGS.
- 3. THE APPROXIMATE DISTANCE FROM THE COMMUNICATION/ELECTRICAL CABINETS TO THE FIRST PULL BOX AT THE NORTHBOUND BOARDING PLATFORM IS 130 FEET.
- 4. ALL PULL BOXES ON THE BOARDING PLATFORMS SHALL BE OZ GEDNEY CAT# YU-161208. SEE ARCH. DWGS FOR BOX LOCATIONS AND QUANTITY OF BOXES.
- 5. SEE UTILITY COMPOSITE UT SERIES DRAWINGS FOR FIBER OPTIC CONDUITS IN COMMON TRENCH AT WEST SIDE OF VAN NESS CORRIDOR.
- 6. MOUNT PA SPEAKERS ON BUS SHELTERS OR CCTV POLES AS DIRECTED BY ENGINEER DURING CONSTRUCTION.
- 7. INSTALL 311 PHONE WIRING VIA NETWORK CONDUITS.


- 8. FOR 311 PHONE INTERCONNECTION BETWEEN STATIONS, SEE TELEPHONE DISTRIBUTION COMPOSITE, DWG CN-027.
- 9. CONTRACTOR TO ORDER ONE AT&T LANDLINE PER 311 PHONE PEDESTAL ON EACH BOARDING ISLAND. TOTAL OF EIGHTEEN (18) AT&T LANDLINES FOR THE 311 PHONE PEDESTALS.
- 10. FOR IRRIGATION POWER AND VARIABLE MESSAGE SIGN POWER, SEE IRRIGATION AND VMS DISTRIBUTION COMPOSITE, DWG CN-028.
- 11. ALL CONCRETE PULL BOXES IN THE SIDEWALK SHALL BE CHRISTY N36 FOR ELECTRICAL POWER, CHRISTY P36 FOR TELEPHONE AND NETWORK SYSTEMS.
- 12. ALL CONDUITS BETWEEN METAL PULL BOXES SHALL BE 1 1/2" HDPE. ALL ABOVE GROUND RIGID CONDUITS SHALL BE 1" RSC IN THE BUS SHELTERS AND SHALL BE CONCEALED. EXPOSED RSC CONDUITS SHALL BE APPROVED BY ENGINEER.




PLAN AT GEARY STREET (NORTHBOUND) CN-15 SCALE: 3/16"=1'



		REVISIONS			
NO.	DATE	DESCRIPTION	REVISED	CHECKED	APPROVED









for the DIRECTOR OF TRANSPORTATION

VAN	NESS	CORRIDOR	TRANSIT	IMPROVEMENT	PROJECT	


MUNI BUS RAPID TRANSIT SYSTEM

BOARDING ISLAND LAYOUT -

CL-29043 REVISION CN-15 CN-31 GEARY STREET STATION NORTHBOUND


1289

BORDER REVISED 11/17/05



- 1. SEE DWG CN-01 FOR VNS ELECTRICAL PANEL SCHEDULE.
- 2. FOR EXACT LOCATIONS OF THE ELECTRICAL EQUIPMENT, SEE ARCHITECTURAL AR-SERIES DRAWINGS.
- 3. THE APPROXIMATE DISTANCE FROM THE COMMERCIAL ELECTRICAL CABINETS TO THE FIRST PULLBOX AT THE NORTHBOUND BOARDING PLATFORM IS 220 FEET.
- 4. ALL PULL BOXES ON THE BOARDING PLATFORMS SHALL BE OZ GEDNEY CAT# YU-161208. SEE ARCH. DWGS FOR BOX LOCATIONS AND QUANTITY OF BOXES.
- 5. SEE UTILITY COMPOSITE UT SERIES DRAWINGS FOR FIBER OPTIC CONDUITS IN COMMON TRENCH AT WEST SIDE OF VAN NESS CORRIDOR.
- 6. MOUNT PA SPEAKERS ON BUS SHELTERS OR CCTV POLES AS DIRECTED BY ENGINEER DURING CONSTRUCTION.
- 7. INSTALL 311 PHONE WIRING VIA NETWORK

- 8. FOR 311 PHONE INTERCONNECTION BETWEEN STATIONS, SEE TELEPHONE DISTRIBUTION COMPOSITE, DWG CN-27.
- 9. CONTRACTOR TO ORDER ONE AT&T LANDLINE PER 311 PHONE PEDESTAL ON EACH BOARDING ISLAND. TOTAL OF EIGHTEEN (18) AT&T LANDLINES FOR THE 311 PHONE PEDESTALS.
- 10. FOR IRRIGATION POWER AND VARIABLE MESSAGE SIGN POWER, SEE IRRIGATION AND VMS DISTRIBUTION COMPOSITE, DWG CN-28.
- 11. ALL CONCRETE PULLBOXES IN THE SIDEWALK SHALL BE CHRISTY N36 FOR ELECTRICAL POWER, CHRISTY P36 FOR TELEPHONE AND NETWORK SYSTEMS.
- 12. ALL CONDUITS BETWEEN METAL PULLBOXES SHALL BE 1-1/2" HDPE. ALL ABOVE GROUND RIGID CONDUITS SHALL BE 1" RSC IN THE BUS SHELTERS AND SHALL BE CONCEALED. EXPOSED RSC CONDUITS SHALL BE APPROVED BY ENGINEER.



NOT VALID UNLESS SIGNED

MAY 1 3 2016

NO. DATE

BORDER REVISED 11/17/05

DESCRIPTION

REVISIONS

REVISED CHECKED APPROVED

for the DIRECTOR OF TRANSPORTATION

CITY AND COUNTY OF SAN FRANCISCO **MUNICIPAL TRANSPORTATION AGENCY**

BOARDING ISLAND LAYOUT — SUTTER STREET STATION NORTHBOUND


MUNI BUS RAPID TRANSIT SYSTEM

VAN NESS CORRIDOR TRANSIT IMPROVEMENT PROJECT

CN-17 CN-31


1289

CL-29045




- 1. SEE DWG CN-01 FOR VNSa ELECTRICAL PANEL SCHEDULE.
- 2. FOR EXACT LOCATIONS OF THE ELECTRICAL EQUIPMENT, SEE ARCHITECTURAL AR-SERIES DRAWINGS.
- 3. THE APPROXIMATE DISTANCE FROM THE COMMERCIAL ELECTRICAL CABINETS TO THE FIRST PULLBOX AT THE NORTHBOUND BOARDING PLATFORM IS 220 FEET.
- 4. ALL PULL BOXES ON THE BOARDING PLATFORMS SHALL BE OZ GEDNEY CAT# YU-161208. SEE ARCH. DWGS FOR BOX LOCATIONS AND QUANTITY OF BOXES.
- 5. SEE UTILITY COMPOSITE UT SERIES DRAWINGS FOR FIBER OPTIC CONDUITS IN COMMON TRENCH AT WEST SIDE OF VAN NESS CORRIDOR.
- 6. MOUNT PA SPEAKERS ON BUS SHELTERS OR CCTV POLES AS DIRECTED BY ENGINEER DURING CONSTRUCTION.
- 7. INSTALL 311 PHONE WIRING VIA NETWORK CONDUITS.


- 8. FOR 311 PHONE INTERCONNECTION BETWEEN STATIONS, SEE TELEPHONE DISTRIBUTION COMPOSITE, DWG CN-27.
- 9. CONTRACTOR TO ORDER ONE AT&T LANDLINE PER 311 PHONE PEDESTAL ON EACH BOARDING ISLAND. TOTAL OF EIGHTEEN (18) AT&T LANDLINES FOR THE 311 PHONE PEDESTALS.
- 10. FOR IRRIGATION POWER AND VARIABLE MESSAGE SIGN POWER, SEE IRRIGATION AND VMS DISTRIBUTION COMPOSITE, DWG CN-28.
- 11. ALL CONCRETE PULLBOXES IN THE SIDEWALK SHALL BE CHRISTY N36 FOR ELECTRICAL POWER, CHRISTY P36 FOR TELEPHONE AND NETWORK SYSTEMS.
- 12. ALL CONDUITS BETWEEN METAL PULLBOXES SHALL BE 1-1/2" HDPE. ALL ABOVE GROUND RIGID CONDUITS SHALL BE 1" RSC IN THE BUS SHELTERS AND SHALL BE CONCEALED. EXPOSED RSC CONDUITS SHALL BE APPROVED BY ENGINEER.




PLAN AT SACRAMENTO STREET (NORTHBOUND) CN-19 SCALE: 3/16"=1'



NO. DATE DESCRIPTION REVISED CHECKED APPROVE REVISIONS BORDER REVISED 11/17/05








CITY AND COUNTY OF SAN FRANCISCO **MUNICIPAL TRANSPORTATION AGENCY**


for the DIRECTOR OF TRANSPORTATION

VAN NESS CORRIDOR TRANSIT IMPROVEMENT PROJECT

MUNI BUS RAPID TRANSIT SYSTEM

CL-29047 CN-19 BOARDING ISLAND LAYOUT -CN-31 SACRAMENTO STREET STATION NORTHBOUND






- 1. SEE DWG CN-01 FOR VNJ ELECTRICAL PANEL SCHEDULE.
- 2. FOR EXACT LOCATIONS OF THE ELECTRICAL EQUIPMENT, SEE ARCHITECTURAL AR-SERIES DRAWINGS.
- 3. THE APPROXIMATE DISTANCE FROM THE COMMERCIAL ELECTRICAL CABINETS TO THE FIRST PULLBOX AT THE NORTHBOUND BOARDING PLATFORM IS 260 FEET.
- 4. ALL PULL BOXES ON THE BOARDING PLATFORMS SHALL BE OZ GEDNEY CAT# YU-161208. SEE ARCH. DWGS FOR BOX LOCATIONS AND QUANTITY OF BOXES.
- 5. SEE UTILITY COMPOSITE UT SERIES DRAWINGS FOR FIBER OPTIC CONDUITS IN COMMON TRENCH AT WEST SIDE OF VAN NESS CORRIDOR.
- 6. MOUNT PA SPEAKERS ON BUS SHELTERS OR CCTV POLES AS DIRECTED BY ENGINEER DURING CONSTRUCTION.
- 7. INSTALL 311 PHONE WIRING VIA NETWORK CONDUITS.

MUNICIPAL TRANSPORTATION AGENCY

for the DIRECTOR OF TRANSPORTATION

- 8. FOR 311 PHONE INTERCONNECTION BETWEEN STATIONS, SEE TELEPHONE DISTRIBUTION COMPOSITE, DWG CN-27.
- 9. CONTRACTOR TO ORDER ONE AT&T LANDLINE PER 311 PHONE PEDESTAL ON EACH BOARDING ISLAND. TOTAL OF EIGHTEEN (18) AT&T LANDLINES FOR THE 311 PHONE PEDESTALS.
- 10. FOR IRRIGATION POWER AND VARIABLE MESSAGE SIGN POWER, SEE IRRIGATION AND VMS DISTRIBUTION COMPOSITE, DWG CN-28.
- 11. ALL CONCRETE PULLBOXES IN THE SIDEWALK SHALL BE CHRISTY N36 FOR ELECTRICAL POWER, CHRISTY P36 FOR TELEPHONE AND NETWORK SYSTEMS.
- 12. ALL CONDUITS BETWEEN METAL PULLBOXES SHALL BE 1-1/2" HDPE. ALL ABOVE GROUND RIGID CONDUITS SHALL BE 1" RSC IN THE BUS SHELTERS AND SHALL BE CONCEALED. EXPOSED RSC CONDUITS SHALL BE APPROVED BY ENGINEER.



NOT VALID UNLESS SIGNEL

MAY 13 2016

BOARDING STATION LAYOUT -JACKSON STREET STATION NORTHBOUND

VAN NESS CORRIDOR TRANSIT IMPROVEMENT PROJECT

CN-21 CN-31

CL-29049


NO. DATE


BORDER REVISED 11/17/05

DESCRIPTION


REVISIONS

REVISED CHECKED APPROVE






, val




w/5




- 1. SEE ARCHITECTURAL AR SERIES DRAWINGS FOR EXACT LOCATIONS OF ELECTRICAL EQUIPMENT.
- 2. MOUNT PA SPEAKERS ON BUS SHELTERS OR CCTV POLES AS DIRECTED BY ENGINEER DURING CONSTRUCTION.
- 3. ALL ABOVE GROUND RIGID CONDUITS SHALL BE 1" RSC IN THE BUS SHELTERS, AND SHALL BE CONCEALED. EXPOSED RSC CONDUITS SHALL BE APPROVED BY ENGINEER.
- 4. SEE ARCHITECTURAL AR SERIES DRAWINGS FOR EXACT LOCATIONS OF ALL METALLIC BOXES ON THE BOARDING ISLANDS, AND QUANTITY OF BOXES.

CN-31



BOARDING ISLAND ELEVATION



NOT VALID UNLESS SIGNED

MAY 13 2016

for the DIRECTOR OF TRANSPORTATION

123


NO. DATE

BORDER REVISED 11/17/05


DESCRIPTION


REVISIONS


REVISED CHECKED APPROVED




y38









LYZ